

Watco Deckgrip

Composition

A urethane alkyd based resin thinned with white spirit. Contains aluminium oxide aggregate.

Appearance

Clear, glossy, gritty finish.

Slip Resistance

BS7976 Pendulum Test Values:
Dry – 73 Extremely low slip potential
Wet – 65 Extremely low slip potential
Surface roughness Rz value: 32µm
An independent test certificate is available.

Availability

2.5 litre tins.

Limitations

Do not apply to a damp surface, or when rain or frost is likely before Watco Deckgrip has completely dried. Wood must be totally dry before application.

Watco Deckgrip is not suitable for heavy duty use or on areas where steel wheeled vehicles will operate. The treated surface may become slippery in very wet conditions or if moss and algae, etc is allowed to build up.

Clear coatings do not give UV resistance to timber. If Watco Deckgrip is applied to unstained timber, the wood will fade to a silver grey finish. A decking stain, such as one of the Watco Decking Oils, should be used before applying this product if a coloured timber finish is required.

Surface Preparation

Surfaces to be treated should be clean, dry and free from mould or any other surface contaminant likely to cause adhesion problems, such as wax, grease, oil etc.

Some pre-treated woods are sealed which can create adhesion problems. Splash on a small amount of water. If beading occurs the surface will need to be lightly sanded, to create a key, or left and re-tested at a later date.

Application

Stir thoroughly with a broad stirrer before use. A short pile roller is recommended but a brush may be used for small areas. Apply two full coats.

Coverage

Approximately 20m² per 2.5L pack per coat

Drying Times

Touch dry in 2-4 hours. Can be recoated after 8 hours. Drying times are based on a substrate temperature of 20°C. Lower temperatures will prolong drying and recoating times.

Safety

Wear suitable gloves. Use only in well-ventilated areas. Avoid release into the environment. Refer to safety data sheets. Contains Cobalt carboxylate, ETHYL METHYL KETOXIME. May produce an allergic reaction. Keep out of the reach of children. Do not empty into drains, dispose of this material and it's container at a hazardous or special waste collection point. If swallowed, seek medical advice immediately and show the container or label.

Storage

Store in a safe place out of the reach of children.

Shelf Life

A minimum of 12 months in unopened containers.

Cleaning of Applicators

Clean applicators or spills with White Spirit.

VOCs

EU limit for this product (cat A1): 600g/l (2007)/500g/l (2010).

This product contains 423g/l VOC.

Ordering

Available direct from Watco UK Limited and through agents worldwide. All Watco products are sold subject to the Company's Standard Conditions of Sale.

The Company and its representatives are often asked to comment on potential uses of Watco products, which differ from those described in the Company's data sheets. Whilst in such cases the Company and its representatives will always try to offer helpful and constructive advice, the Company cannot be held responsible for the results of such use unless they are specifically confirmed in writing by Watco.

Also available
from Watco

Floor Paints & Coatings

Dustproofers & Sealers

Line Marking

Flooring

Anti Slip Coatings

Anti Slip Products

Floor Repair Materials

Screeds

Preparation Materials

Masonry Repair Materials

Wall Coatings

Exterior Products

Traffic Control

Metal Coatings

Roofing

WATCO®

Watco UK Limited

Watco House, Filmer Grove, Godalming, Surrey GU7 3AL, UK
Tel: 01483 42 5000 • Fax: 01483 42 8888
www.watco.co.uk • E-mail: sales@watco.co.uk

Quality Certified

ISO 9001
BUREAU VERITAS
Certification



Designed, manufactured and supplied under an ISO 9001 quality management system